

D-CAM 600 series

D-CAMTM 600

Integrated Camera, PIR & Timer Video over UTP (optional)



Get
the Whole
Picture



You Can't Tell it's a Camera! Ideal for Covert Surveillance

- Sleek new design
- High quality color or b/w video
- Invisible Camera hole
- Covered LED indicators
- Unshielded Twisted Pair (UTP) transmission (optional)
- Suited for low lighting conditions going as low as 0.003 Lux
- Built in smart timer
- High quality microphone with built-in amplifier (optional)
- Environmental immunity
- Fast mounting

The **D-Cam 600** comes in a new slim design, with the almost invisible camera hole underneath the surface. There are a variety of models – some are equipped for recording in very low lighting conditions – from 0.003 LUX, while others provide the option of video transmission over unshielded twisted pair UTP (please see back for more details).

These features make the **D-Cam 600** ideal for covert surveillance - the presence of a camera is undetectable to the human eye.

The **D-Cam 600** units are ideal as add-on cameras for security installations, feeding to CCTV Monitors, Transmitters and DVRs.

The **D-Cam 600** series features high-quality, high-sensitivity pinhole camera, PIR sensor and adjustable timer, covertly packed in a standard PIR casing with matching fields of view for the camera and the PIR sensor.

D-CAMTM600

Integrated Camera, PIR & Timer Video over UTP (optional)

Video over Unshielded Twisted Pair (UTP)

Our Video over UTP models save you the need for expensive, rigid coax cables for Video transmission from the D-Cam 600 to the recording/monitoring unit.

They support transmission of video signals over unshielded twisted pair up to at least 100 m (300 feet) away.



These models come with a built-in Balun*, and we supply an additional Balun – a Passive unit with BNC Connector - to be used at other end.

*A Balun is a Balanced to Unbalanced Passive device for transmission over UTP



Ordering information

D-Cam 600/C 15512507	Color CCD Camera 0.5 Lux Swivel bracket included
D-Cam 600/B 15512508	B&W Digital Camera 0.1 Lux Swivel bracket included
D-Cam 600/BX 15516508	B&W Digital Camera 0.003 Lux Swivel bracket included
D-Cam 600/TC 15520507	Built-In Video Transmission over twisted pair Color CCD Camera 0.5 Lux Balun (converter) for Receiving included Power supply & swivel bracket included
D-Cam 600/TB 15520508	Built-In Video Transmission over twisted pair B&W CCD Camera 0.1 Lux Balun (converter) for Receiving included Power supply & swivel bracket included
D-Cam 600/TBX 15526508	Built-In Video Transmission over twisted pair B&W CCD Camera 0.003 Lux Balun (converter) for Receiving included Power supply & swivel bracket included

*Also available with built-in microphone



Specifications

Camera	B&W				COLOR	
Model	BW	BWX	BWT	BWXT	C	CT
TV Standard	CCIR / EIA				PAL / NTSC	
Resolution	420 lines				380 lines	
Sensitivity	0.1 Lux (F2.0)	0.003 Lux (F2.0)	0.1 Lux (F2.0)	0.003 Lux (F2.0)	0.5 Lux (F2.0)	0.5 Lux (F2.0)
S/N Ratio	Better than 48dB					
Shutter Control	Automatic 1/50 – 1/10,000					
White Balance	Auto white balance					
Pinhole Lens	F4.3mm standard					
Video over Twisted Pair (VTP)	No	No	Yes	Yes	No	Yes
Including Balun	No	No	Yes	Yes	No	Yes
Detector	Dual Element PIR, ASIC based					
Lens Type	Hard spherical lens					
Sensitivity	$\Delta 1.6^{\circ}\text{C}$ ($\Delta 3^{\circ}\text{F}$) @ 0.6m/sec (2ft/sec)					
Detection Speed	0.3 - 1.5m/sec (1 - 5ft/sec)					
Temp. Compens.	Bi-directional					
Pulse Count	Jumpers selection: 1- 3 pulses for normal to high-risk operation					
Coverage	Wide angle 90° 18m x 18m (60ft x 60ft)					
RFI Protection	30V/m 10 - 1000MHz					
EMI Protection	50,000V of electrical interference from lighting or power through					
Output Relays						
N.C.	28VDC, 0.1A with 20ohm serial resistor					
	Momentum opening for min. 1.6 sec upon detection					
N.O.	28VDC, 0.1A with 20ohm serial resistor					
Timer	N.O.					
	Retriggable closure, adjustable from 10 to 100 secs.					
Audio	Optional					
Power Supply	B&W				COLOR	
Operating Voltage	11 - 13 Vdc					
Current Draw	130mA @ 12Vdc Typical				170mA @ 12Vdc Typical	
Op. Temperature	-10 - 50°C (23 - 122°F)				0 - 40°C (32 - 104°F)	
Dimensions	137 x 65 x 49 mm (5.4 x 2.6 x 1.9 inch)					
Weight	140gr (5oz.)					

Headquarters
Video Domain Technologies Ltd.
Tel: 972-3-904-4111
Fax: 972-3-904-3003
sales@vdomain.com

USA Sales Office
Video Domain Technologies Inc.
Toll Free: 866-MEMOCAM (636-6226)
Tel: 201-735-0429
Fax: 866-422-1105
sales-us@vdomain.com

UK Sales Office
VDT (UK) Ltd.
Tel: 0870-330-0166
Fax: 0870-330-0167
sales-uk@vdomain.com

www.vdomain.com